Remote Cargo Hook Test Form
R66

DART AEROSPACE

Work Order _____   Customer _____

Serial Number _____   Date _____

# of Releases	Load (Lbs.)	Release Method	Remarks	Result	Pass/Fail
1	2,537	Static Hold	Hold for two Minutes and reduce load to zero	N/A	
10	507	Electircal, 25 volts	No "hang ups" permitted	N/A	
2	1,015	Electircal, 22 volts	Current shall not exceed 13.0A	A	
2	515	Electircal, 22 volts	Current shall not exceed 13.0A	A	
2	500	Electircal, 22 volts	Current shall not exceed 13.0A	A	
2	250	Electircal, 22 volts	Current shall not exceed 13.0A	A	
2	50	Electircal, 22 volts	Current shall not exceed 13.0A	A	
1	1,015	Electircal, 20 volts	Current shall not exceed 13.0A	A	
1	1,015	Electircal, 28 volts	Current shall not exceed 13.0A	A	
1	1,015	Manual		N/A	
1	1,015	Impact Test		N/A	
1	N/A	Solenoid Ohms	Shall not exceed 2.1 - 2.4 Ω	Ω	
1	N/A	Electircal Continuity	Across both wires	N/A	

Test Conducted By: _____   Signature _____

Technician   QC 5 Small FAB / QA